

## **XL BLADEMATE**



- 53-foot trailer opens to 184 feet with bumper
- Steel treadplate fenders available on the front and rear
- Add 24" long bunks to provide additional loading areas across the main beams: rolling and adjustable non-rolling versions available
- Rear-facing worklight at front, rated at 1200 lumens
- Red/green indicator lights on the toolbox front and rear signal if the power unit is on or off
- Air and electrical lines are well-protected inside turn table plates to keep them clean



## trail

### **SELF-STEERING SYSTEM**

The axles automatically rotate to keep the trailer behind the truck at all times; the kingpin rotates and prompts the axles to track with it. An override remote allows drivers to take full control as needed. A beacon light alerts the driver and pilot car when the axles are turning (past 3 degrees).

### **CONVENIENT EXTENSION**

XL's trusted extendable technology is the key to hassle-free extension; all trailer beams as well as the pullout bumper are on greasable rollers. Experience the smooth, quick, convenient extension of an XL with the Blade Mate. Extend from 53 feet to 184 feet with the pullout bumper.

DESIGNED FOR YOU. BUILT TO LAST.

# BLADEMATE

### **CAPACITY**

capacity: 90,000 lb overall weight: 33,350 lb without bunks 35,140 lb with 2 bunks

### **OVERALL LENGTH & WIDTH**

overall length: 53' closed, opens to 184' 2" with pullout bumper overall width: 102"

### **GOOSENECK**

9' long
19" king pin setting
77" swing clearance
49" 5th wheel height
2 speed landing gear with handle
on curbside
bolt-on aluminum front fenders
2 d-rings on front
2 d-rings per side - 4 total
4 d-rings on rear of platform
20" loading platform on front
57" deck height on platform
1 pair of flag holders

### **MAIN DECK**

T-1 flange, 80K web
13HP hydraulic power unit
51" loaded deck height
20" steel platform at rear with 4
d-rings and 6 chain slots
telescoping main frame,
4 total sections with stops on
18" centers after total
extension of 124"
2 pairs of flag holders
20' pullout, non-load bearing
bumper with stops on 24"
centers
1 pair d-rings in tail channel

### **MAIN DECK OPTIONS**

24" long rolling bunk 24" long adjustable non-rolling bunk deck inserts

### **SUSPENSION**

25,000 lb air ride raise and lower valve manual ride height control

### **SUSPENSION OPTIONS**

liquid filled air gauge Air-weigh digital scale

### **AXLES**

(3) 25,000 lb nominal
71" spacing
hub pilot, outboard drums
2SIM ABS
12 1/4" x 7 1/2" brakes
1 pair spring brakes
Tritronic hydraulic control kingpin
steering system with wireless
remote for over steering

### **AXLE OPTIONS**

hubometer
TP axles (same inner & outer bearings)
dust shields
cat eye systems
disc brakes

### **WHEELS & TIRES**

6.75 x 17.5 steel rims 245/70R/17.5 tires

### **WHEEL & TIRE OPTIONS**

customer specified tires customer specified mud flaps aluminum mill wheels aluminum polished wheels Michelin tires PSI tire inflation system

### **LIGHTING**

12V sealed Grote harness
rubber mounted LED lights
3 tail light package with
aluminum cover
amber strope as 3rd stop turn tail
rear facing work light on upper
deck
power on/off indicator
system alignment indicator

### **PAINT**

black, IH red, CAT yellow or white air & electric done after paint

### **PAINT OPTIONS**

non-standard paint colors non-standard metallic paint

### **WARRANTY**

5 year structural 3 year paint

### **AVAILABLE MODELS**

**XL 90 BM**