

XL GUARDIAN: 110 LOW-PROFILE HDG

FEATURES

• Gooseneck relief cut-out allows truck fenders to clear

PECIALIZED

- Many securement options: D-rings, chain slots
- Availible in 18" & 22" loaded deck height
- Front pull out outrigger
- Bucket well and open boom trough
- Trilliant work light in gooseneck
- Bolt-on wheel cover options available


EQUIPMENT-READY MAIN DECK

The trailer's 26-foot-long, 8-foot-6-inch-wide main deck is constructed with a fully welded I-beam design, using 100K flanges and 80K webs, as well as upper-flange reinforcement. The rugged, raised apitong decking is built to last, while a toolbox located in the front provides a place to store chains and other materials.

VERSATILE AXLE CONFIGURATIONS

The Guardian is a 3-axle trailer that can be run by itself or with an added flip axle, a spreader bar and flip, a single-axle power booster or a hydraulic flip axle. XL's new bolt-on recessed hydraulic flip axle option houses the hydraulic cylinder, quickly flipping the axle without the need for a forklift. This allows for better loading clearance over the flip axle and easy swapping between flip axles and boosters.

DESIGNED FOR YOU. BUILT TO LAST. www.xlspecializedtrailer.com | 877.283.4852



GUARDIAN: 110 HDG

CAPACITY

capacity: 110,000 lb overall concentrated: 110,000 lb in 12'

OVERALL LENGTH & WIDTH

overall length: 53' overall width: 102"

GOOSENECK

13' low-profile style neck with relief cut-out
51" 5th wheel height
5 position variable ride height
110" & 84" swing clearance
16" & 42" king pin setting hydraulics run off wet kit
air operated lock with manual safety latch
trilliant work light
toolbox in rear of neck with aluminum cover
registration holder

GOOSENECK OPTIONS

13HP power unit, base of neck, dual hydraulics chain rack inside toolbox

MAIN DECK

26' long T-1 flange, 80K web (4) 16" fabricated i-beams 18" loaded deck height or 22" loaded deck height 6"ground clearance 18" HDG: (4) 12" fabricated i-beams 22" HDG: (4) 16" fabricated i-beams jr. i-beams on alternating 12" centers top flange reinforcement 31" front flip ramps 7 bent d-rings per side 1 3/8" Apitong decking - raised, open center
toolbox in front of deck
4 flat d-rings in toolbox
chain drops on 24" centers
heavy-duty swing out outriggers on 24" centers, double in center
heavy-duty front pull out outrigger
1 pair EZ mount flag holders

1 pair EZ mount flag holders bucket well at rear, plate on bottom 4 flat d-rings in bucket well

REAR DECK

14' long with 32° rear transition 18" HDG: 41" loaded deck height bolsters dropped 4" down 22" HDG: 40" loaded deck height open wheels - bolster style open boom trough air lift on 3rd axle 16 1/2" X 7" brakes auto slack adjusters 54 1/2" axle spacing limit chains on all axles 1 pair flat d-rings on main beams at front 1 pair flat d-rings on main beams at rear 2 pair flat d-rings in boom trough 2 chain drops on each bolster 1 pair EZ mount flag holders 2 stake pockets in tail channel for wide load sign prep 1-axle booster (1) 4-way plug at rear covered boom trough, bolt-on bottom plate battery back-up w. 4-way plug for FA **REAR DECK OPTIONS**

prep for power booster prep for hydraulic flip axle w/ air lock pins

removable wheel covers heavy-duty, load bearing removable wheel covers medium-duty,

non-load bearing

SUSPENSION

25,000 lb air ride raise and lower valve manual ride height control liquid filled air gauge

AXLES

(3) 25,000 lb nominal spring brakes on 1 axle ABS not required

WHEELS & TIRES

8.25 x 22.5 steel inside, aluminum polished outside rims255 / 70R / 22.5 tireshub pilot, outboard drums

LIGHTING

12V sealed Grote harness
rubber mounted LED lights
3 tail light package with aluminum cover
4" amber stobe as 3rd tail light
4 clearance lights per side

at rear, 1 at front, 2 on main deck

1 mid-turn light per side
7 pole electric socket

PAINT

black air & electric done after paint

WARRANTY

5 year structural 3 year paint

DESIGNED FOR YOU. BUILT TO LAST. www.xlspecializedtrailer.com | 877.283.4852