



XL DEFENDER: 90 HDE



FEATURES

- Extendable deck accommodates extra-long loads
- Gooseneck features a 7-position adjustable ride height for added versatility
- Built-in brackets support a 36" flip neck, with optional flip neck available
- Hydraulic neck enables fast and efficient loading and unloading
- Reinforced frame to support a booster
- Extension stops positioned every 2 feet for precise length adjustment



VERSATILE & RUGGED MAIN DECK

The XL 90 HDE Defender deck is built to handle a wide range of hauling needs with exceptional durability. It features chain drops spaced every 24 inches along the outer beams, eight bent D-rings on each side, and removable swing-out outrigger brackets with the option to add outriggers for more versatility. Its Apitong wood decking provides long-lasting resistance to wear, making it a reliable choice for demanding jobs.


INNOVATION IN EXTENDABLE TRAILER DESIGN

Leading the way in extendable trailer technology, the XL Extend-A-Trac system offers a seamless extension and retraction process without the need to disconnect air and electrical lines. With extension stops every two feet, users can adjust the trailer to various lengths as needed. The design includes six-inch greaseable rollers with oil-impregnated bronze bushings, ensuring smooth, low-maintenance operation.

DESIGNED FOR YOU. BUILT TO LAST.

www.xlspecializedtrailer.com | 877.283.4852

XL 90 HDE DEFENDER SPECS



XL 80 HDE CAPACITY

capacity: 90,000 lb overall
concentrated: 35,000 lb in 5' at front
and rear of main deck, fully extended
(70,000 lb total)

OVERALL LENGTH & WIDTH

overall length: 48' or 53'
overall width: 102"

GOOSENECK

hydraulic detachable (classic)
10' 5" long
16" kingpin setting
84" swing clearance
49" 5th wheel height
7 position variable ride height
hydraulics run off wet kit
air operated lock with manual
safety latch
brackets for 36" flip neck
registration holder

GOOSENECK OPTIONS

13HP power unit, base of neck,
aluminum cover, dual hydraulics
36" flip neck

MAIN DECK

48' OAL: 28' 7" - 49' 11" long - 30"
stationary deck
53' OAL: 33' 7" - 59' 11" long - 30"
stationary deck
extension stops on 24" centers
T-1 flange, 80K web
(4) 14" fabricated i-beams
20" loaded deck height
6" ground clearance
6" jr i-beam & knee braces
on 12" alternating centers

8 bent d-rings per side
1 1/8" Apitong decking - flush,
center covered
ramp tapers to 4"
chain drops on 24" centers,
outside beams
removable swing out outrigger
brackets on 24" centers
2 flag holders at front

MAIN DECK OPTIONS

removable swing out outriggers

REAR DECK

9' long
40" loaded deck height
1 1/8" Apitong decking - flush
2 flag holders
2 pan style d-rings per side, on
corner
1 pair flat d-rings on rear transition
2 bent d-rings in tail channel
prep for 2 axle booster

REAR DECK OPTIONS

battery back up w/ 4-way plug

SUSPENSION

25,000 lb air ride
raise and lower valve
manual ride height control
liquid filled air gauge

AXLES

(2) 25,000 lb nominal
54" axle spacing
hub pilot, outboard drums
4S2M ABS
16 1/2" x 7" brakes
2 pair spring brakes

WHEELS & TIRES

8.25 x 22.5 steel inside rims
8.25 x 22.5 aluminum polished
outside rims
255 / 70R / 22.5 tires

LIGHTING

12V sealed Grote harness
rubber mounted LED lights
3 tail light package with
aluminum cover
4" amber strobe used as 3rd tail light
(3) 3/4" LED clearance lights per side
1 mid-turn light per side
7 pole electric socket

PAINT

black
air & electric done after paint

WARRANTY

5 year structural
3 year paint

DESIGNED FOR YOU. BUILT TO LAST.

www.xlspecializedtrailer.com | 877.283.4852